



### SPECIAL FEATURES

- Aluminum Pull-outs: Multi-positions to 13' wide
- 1-1/2" Apitong Decking
- Self-Centering Gooseneck Support (no truck frame modification needed- Patent Pending)
- Five Gooseneck/Deck adjustment heights
- Two lockable toolboxes on front of gooseneck
- One lockable toolbox back of gooseneck
- Adjustable air ride—height 3 positions-1" intervals
- **OPTIONAL:**
- 3<sup>rd</sup> Axle Flip
- Main deck to rear deck ramps
- Honda Hydraulic Pony Motor
- Electric over Hydraulic system

### SPECIFICATIONS:

• <b>WEIGHT</b>	17,700 lbs ± 3%
• <b>CAPACITY</b>	70,000 lbs in 16'
• <b>LENGTH OVERALL</b>	48'
• <b>LOADED DECK HEIGHT</b>	20"
• <b>LOADED GROUND CLEARANCE</b>	6"
• <b>OVERALL WIDTH</b>	102"
• <b>DECK LENGTH</b>	29'
• <b>GOOSENECK LENGTH</b>	10' 5"
• <b>SWING CLEARANCE</b>	84"
• <b>BEAM TYPE</b>	T-1 Flanges Manufactured 80K Webs
• <b>BRAKES</b>	7" X 16 1/2" ABS 2s/1m
• <b>TIRES</b>	255/70R X 22.5-----16 Ply Radials
• <b>WHEELS</b>	8.25 X 22.5
• <b>AXLES</b>	22.5K
• <b>SUSPENSION</b>	Air Ride
• <b>AUTO SLACK ADJUSTMENT</b>	Standard
• <b>15" KING PIN SETTING</b>	King Pin 2" SAE
• <b>TIE DOWNS</b>	Pockets & D-Rings
• <b>MUDFLAPS</b>	Yes
• <b>WIRING</b>	Sealed Modular Wiring Harness
• <b>LIGHTING</b>	LED Lighting
• <b>FINISH</b>	Sand blasted, primed and painted (Black)
• <b>ALUMINUM CROSSMEMBER</b>	8" Deep 18" Centers (Patent Pending)
• <b>FINANCING/LEASING AVAILABLE:</b>	<b>Stearns Bank 1-800-247-1922 ext 163 Jim Peach</b>

Manufacturer reserves the right to modify with out notice specific design and specifications as deemed advisable on the trailers described herein w/o obligation to trailers previously sold. Written warranty covers each trailer, no other warrant expressed or implied. Warranty on tires and brakes through original manufacturer. All dimension and weights are approximate